SP ProLevel® 10

Flatness and Level Starter Package





Content of Flatness and Level Starter Package

SP ProLevel® 10

T330 Self Levelling Sweep Laser (BG 830203)



The T330 levelling laser makes even difficult measuring tasks easy! A laser transmitter transmits the signal and a detector measures the beam position. Done!

R310 Laser receiver (BG 830134)



The R310 measures the position of the rotating laser beam. The CCD Sensor has total measurement range of 80mm. The beam forms an entire reference plane. The R310 is wireless and can measure up to a distance of 80m from the Laser.

Accessories: BG 830136 Battery Compartment without Bluetooth

BT 800071 Battery Pack Li-Ion BT 800072 Battery Charger

RC310 Remote Control for T330 and R310 Monitor (BG 830930)



- Remote control for the T330
- Remote Display of current R310 values

The RC310 is of great practical use in most applications:

- for establishing reference lines in roll parallelism
- · for adjusting the T330 laser position
- it saves you a great deal of shoe leather on-site



Mounting Kit for T330 (BG 830205)



Using the swivel and tilt adapter you can align the laser level, irrespective of the surface below. The Adapter also allows for a parallel movement which is very useful when aligning the laser parallel to a reference object. The Adapter is accomodated with a 5/8" thread, and is also fitted with a three-point magnet arrangement underneath.

Power supply cable for T330 (BG 800026)



Power supply cable for the T330 with straight plug.

12 V, 450 mA incl. adapter

Switch magnet with prism bottom $-60 \times 50 \times 55 \text{ mm} - \text{M8} - 750 \text{N}$ (BT 943105)



Block magnet for many measuring and fixing tasks. The upper surfaces has an M8 thread for attachment purposes. Dimensions: $60 \times 50 \times 55$ mm, 750N

Screw adapter M8 (BT 948336)



Screw adapter with an M8 thread to enable the R310 or R280 to be mounted on different objects.

Installed adapter length: 30 mm

Laser kit Case small with foam inlays – version T330 (BG 990100)



Rugged Case IP65 with wheels and telescope handle. The small case is complete with the following main foam inlays:

- BT 990020: Foam inlay for R310, R5XX
- BT 990027: Foam inlay for UMPC
- BT 990029, BT 990030: Foam inlay for T330

Please contact us for further informations or questions.





Status Pro Maschinenmesstechnik GmbH Mausegatt 19 D-44866 Bochum Phone: + 49 (0) 2327 - 9881 - 0

Fax: +49 (0) 2327 - 9881 - 81

www.statuspro.com info@statuspro.com

PC 1021E 11/13 · Design / DTP: Seichter & Steffens Grafikdesign, D-44229 Dortmund. Copyright 2013 Status Pro Maschinenmesstechnik GmbH. ProLevel® is a registered trademark and subject to trademark rights of Status Pro Maschinenmesstechnik GmbH. This document or parts thereof may not be copied or otherwise reproduced without the

permission of Status Pro GmbH. The technical details are subject to change without notification.

We would appreciate being informed of any errors in this document.

Distributor		